SPECIFICATIONS: 16SGB

Dimensions:	U.S.	Metric:
Weight	406 lbs	184.16 kg
Height	54.5"	1.38 m
Length	74"	1.88 m
Width	29"	.74 mm
Engine Options*:		
Honda (HP: 11.7)	GX390	GX390
Briggs Vanguard	16hp V-Twin	16hp V-Twin
Fuel	Gasoline	Gasoline
Additional Specs:		THE I

Head Swing Heavy Duty Centrifugal Clutch Drive

35°, 20" arc double 5/8" belt

Establishing Bassie

134°, .51m arc



kg

16SGB MINI STUMP GRINDER

DESIGN

The latest additions to the Barreto Tree Care Family are the new 13SGH and 16SGB stump grinders. The stump grinders' unique design pivots over the center line of the wheels, allowing the grinding head to sweep easily across the stump, while the wheel base remains stationary. Engine options include the Honda GX390 or the 16hp Briggs & Stratton Vanguard V-Twin. The innovative design and compact stature of this stump grinder makes it ideal for tight access areas. The swivel head has a swing arc of 35° and the cutting wheel has eight carbide green teeth with three cutting surfaces. Free-wheeling hubs facilitate easy travel to the jobsite, while the independent wheel locks allow for easy locking while grinding.

CONTROLS

The height of the 13SGH/16SGB operator control handlebar can be easily adjusted to suit both the operator and the grinding situation. The cutter wheel is operated by the handlebar-mounted safety bale and a fully throttled engine. The handle bale acts as a secondary safety switch to prevent accidents. The operator uses the handlebars to manually control the head swing and depth of cut.

ROI

With a unique design that provides limited need for maintenance and repair, these stump grinders will remain in the field getting the job done instead of tying up your revenue and mechanic. Because Barreto stump grinders are reliable in difficult conditions, customer satisfaction is high.

FEATURES



Save time, money, and maintenance with the eight carbide green teeth that have three cutting surfaces each.



The innovative pivot over center swivel head design allows the grinding wheel to sweep easily across the stump.



Easy to operate controls are located on the adjustable-height handle bar, and the safety lever requires operator presence.

CONTACT US 1-800-525-7348 info@barretomfg.com

